



Excellent Water or Condensate to 65% Up to 4x the Foam of Regular Stick
Main Stick Used in Conjunction with Gas Stick to Kick off Dead Wells

SUPERFOAM SOAP STICKS are special foam sticks that contain 100% active surfactants, friction reducer and foam stabilizer in water-soluble tubes. Natural gas bubbling through the water column and 100% active ingredients produces foam which can help remove water from watered-up gas wells.

PRODUCT USES & ADVANTAGES:

SUPERFOAM SOAP STICKS are primarily used to remove water from gas wells and increase gas production. This foaming action decreases the hydrostatic back-pressure which increases gas production that further enhances the foaming action until the well unloads

SUPERFOAM SOAP STICKS can be used to **remove fluid from gas-condensate wells and flowing oil wells.** For gas-condensate wells with more than 65% condensate, it is recommended to use **OIL FOAM (CONDENSATE) STICKS™** in conjunction with **SUPERFOAM SOAP STICKS.**

SUPERFOAM SOAP STICKS contains 100% active foamer in a water soluble tube that can produce up to four (4) times more foam than some other sticks on the market. These sticks can develop stable foam in high temperature deep gas wells. Lab tests indicate that stable foam can be developed at 212 degrees Fahrenheit and above. For extremely high temperature wells the formulation can be altered.

SUPERFOAM SOAP STICKS are used in water injection wells in combination with **ACID STICKS®** to help reduce injection pressures. Surfactants contained in **SUPERFOAM SOAP STICKS** can help remove oil coatings on scale. This helps the **ACID STICKS®** react with the exposed scale.

SUPERFOAM SOAP STICKS are an economical way to remove water from gas wells without using expensive well service operations such as swabbing, jetting with coiled tubing, or installing artificial lift and siphon strings.

TREATMENT DETERMINATION & PROCEDURE

The number of **SUPERFOAM SOAP STICKS** used is based on the volume of water above the perforations. Field tests indicate that the best results were achieved by using a larger initial slug treatment of 1/8 to 1/4 % by weight of sticks to water above the perforations. **A treatment of 1/8 to 1/4 % by weight would require .44 to .88 lb of stick per BBL of water.**

PART NUMBER	STICK SIZES	STICK RATIO INITIAL SLUG TREATMENT
ACL-5020	3/4 X 15	2 TO 4 STICKS PER 1 BBL's OF Total Fluid
ACL-5035	1 X 15	2 TO 3 STICKS PER 1 BBL's OF Total Fluid
ACL-5045	1 1/4 X 9	2 TO 4 STICKS PER 1 BBL's OF Total Fluid
ACL-5050	1 1/4 X 15	1 TO 2 STICKS PER 1 BBL's OF Total Fluid
ACL-5065	1 1/4 X 18	1/2 TO 1 STICKS PER 1 BBL's OF Total Fluid
ACL-5070	1 3/8 X 5 1/2	2 TO 4 STICKS PER 1 BBL's OF Total Fluid

ALTACHEM LTD.

5507-76th Ave. EDMONTON, AB. T6B 0A7

Cell: (780) 907-2357 (Peter)

FAX: 780-414-1446

Email: altachem@shaw.ca

PH: 780-414-1445
www.altachem.ca

TF: 1-866-414-1445
www.altachem.net



Tech Data Sheet
ACL-50 (AC-50) SERIES

SUPERFOAM SOAPSTICK
WATER SOLUBLE TUBE (OFF YELLOW)

Tech Data Sheet
PAGE 2 OF 2

NOTE:

The above amount is recommended for an initial slug treatment. In many cases, *removing the top few hundred feet of fluid may be sufficient to allow the production of natural gas to blow out the remaining fluid in the well.* To determine the optimum amount for periodic treatments you may choose to gradually reduce the initial treatment amount until the most economical point is reached. Periodic treatments with **SUPERFOAM SOAP STICKS** may be necessary to prevent production decline due to the gradual water build-up. It is much easier to maintain gas production with regular insertion of **SUPERFOAM SOAP STICKS** than it is to kick off a dead well. Gas bubbling through water is necessary to create foam. If a well is totally dead, **GAS STICKS™** may be used in conjunction with **SUPERFOAM SOAP STICKS** to provide agitation energy.

THE MOST COMMON PROCEDURE

Is to shut-in the well and drop sticks through a lubricator. *Wait 45 seconds until sticks contact top of fluid then slowly return well to normal production.* Repeat procedure if or when it becomes necessary. FOR HIGH RATE WELLS (after sticks have contacted the top of fluid) flow well at about 25% of pretreatment rate for about 20 minutes or until foam reaches surface then return to normal rate. **FOR SHALLOW OR LOW RATE WELLS leave well flowing while dropping sticks if possible.**

PRODUCT SPECIFICATIONS

The stick will normally *dissolve in 20 to 80 minutes depending on temperature*, salt content, and relative water motion. **SUPERFOAM SOAP STICKS are 100% soluble in water** and insoluble in oil. The melting point of the sticks is 122°F. The stick will dissolve in water in wells with BHT below 122° (just at a slower rate). Lab tests indicate the dissolving rate in 50,000 PPM moving brine water to be 72 minutes @ 100°, 25 minutes @ 120°, 8 minutes @ 140°, and 3 minutes @ 180°. The dissolving time will decrease if the sticks are broken before dropping or if they break upon impact with the top of the fluid. The specific gravity is 1.11. *The falling rate through fresh water is approximately 100 feet per minute. The sticks can free fall (through air) 3,000 feet in about 15 seconds.* Gas moving up tubing will often change falling characteristics.

FOR INDUSTRIAL USE ONLY:

CAUTION: As with all industrial chemicals, contact with eyes or skin should be avoided. Wash thoroughly with water. Pellets should be stored in a cool dry place. Always remove pellets from the container with the scoop provided while wearing rubber gloves to avoid skin contact. Goggles are advised.

ALACHEM LTD.

5507-76th Ave. EDMONTON, AB. T6B 0A7

Cell: (780) 907-2357 (Peter)

FAX: 780-414-1446

Email: altachem@shaw.caPH: 780-414-1445
www.altachem.caTF: 1-866-414-1445
www.altachem.net