OILFIELD & INDUSTRIAL CHEMICALS

ALTACHEM LTD.
ACL-FT50 (AC-FT50)

FOAMTEK 50 (Low-Medium Well Foamer)

Tech Data Sheet

PROPERTIES:

<u>Foamtek 50</u> is a winterized biodegradable foaming agent blended to aid in unloading produced water in gas wells. <u>Foamtek 50</u> is a biodegradable foaming agent especially formulated for economical use. It is an excellent drilling foamer and is useful as an aid for unloading gas wells.

PRODUCT BENFITS:

- Highly stable foam designed to maintain an optimum volume of water through the separator.
- Concentrated to be economical resulting in low usage rates.
- Effective Removal of Water
- Effective in all Types of Water
- Blended to -45°C
- Cost Effective

PRODUCT DATA:

For an extensive list of physical properties, refer to the SDS.

P/H = 7.5 +- 0.5
 Color: = Clear
 Specific Gravity: = 0.97 +- 0.02
 Scent: = Slight Alcohol

Stability = Highly Stable (> 1 Year)
 Storage: = Store in a Cool Dry Place

DIRECTIONS:

FOAM TEK 50 can be injected or batched into well. Treatment Rates are usually determined by the Well Operator initially starting with a higher amount and slowly decreasing the injection rates till an optimum rate is achieved. This is done over a week period to achieve your highest level of optimization. Typical treating dosage is 5 - 10 % by volume depending on severity of water influx. This product can be continuously injected at a rate of 10 ¬50 ppm.

PACKAGING:

This product is available in packages of: 20L, 205IL, 1025L Totes

GENERAL FIRST AID INFORMATION

IN CASE OF INHALATION

Remove victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel. Immediately transport victim to an emergency care facility.

IN CASE OF INGESTION

Rinse victim's mouth with water. DO NOT INDUCE VOMITING. Have victim drink 300 mL of water to dilute material in stomach. If milk is available, it may be given AFTER the water. Transport to an emergency facility.

ALTACHEM LTD.
5507-76th Ave. EDMONTON, AB. T6B 0A7
Cell: (780) 907-2357 (Peter)
FAX: 780-414-1446
Email: altachem@shaw.ca

OILFIELD & INDUSTRIAL CHEMICALS

FOAMTEK 50 (Low-Medium Well Foamer)

Tech Data Sheet

GENERAL FIRST AID INFORMATION

IN CASE OF CONTACT WITH SKIN

In case of contact with skin, remove contaminated clothing and flush with water for at least 60 minutes. Do not interrupt flushing. Transport to an emergency facility.

IN CASE OF CONTACT WITH EYES

In case of contact with eyes, continuously flush eyes with plenty of water or neutral saline solution for at least 60 minutes. Transport to an emergency facility.

PERSONAL PROTECTIVE EQUIPMENT REQUIRED IF HANDLING DIRECTLY

Impermeable gloves
Chemical goggles or safety glasses
NIOSH approved when misted
Regular Safety Boots
Eye Wash Station

TDG:

UN 1992 Flammable liquids, toxic, n.o.s (Methanol, ethanol), Class 3, PG II

Preparation of TDS

Altachem Ltd. believes that all statements, technical information and recommendations contained herein are based on available scientific tests or data which we believe to be reliable. The accuracy and completeness of such data are not warranted or guaranteed. We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. ALTACHEM assumes no liability or responsibility for loss or damage resulting from the improper use or handling of our products, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the product's label and Safety Data Sheet.

For further details on the source of this information, see SDS.

ALTACHEM LTD.
5507-76th Ave. EDMONTON, AB. T6B 0A7
Cell: (780) 907-2357 (Peter)
FAX: 780-414-1446
Email: altachem@shaw.ca

PH: 780-414-1445 www.altachem.ca TF: 1-866-414-1445 www.altachem,net